



Technical Specifications

Operation mode	Adds CO ₂ and N ₂ to Air
Concentration Range	CO ₂ : 0-10%; O ₂ 1-18%
CO ₂ Accuracy	± 5% of CO ₂ concentration, i.e. ± 0.25% at 5% CO ₂
O ₂ Accuracy	0.1% at 5% O ₂
Set point resolution	0.1%
CO ₂ Repeatability	Better than 0.1%
O ₂ Repeatability	0.05% of O ₂
Total Flow rate, NL/min	0.2-0.8 NL/min
Outlet Pressure	Ambient
CO ₂ Consumption	0.02 at 5% CO ₂ and 0.4 NL/min total flow rate
N ₂ Consumption	0.3 at 5% O ₂ and 0.4 NL/min total flow rate
CO ₂ Sensor	Non Dispersive InfraRed (NDIR) dual wave length detector
O ₂ Sensor	Zirconium oxide
Sensors Life	10 years
Input and Output Gas connectors	6 mm OD push in fittings
Dimensions, mm	348x290x140
Weight, g	7600 g
Compatible with	H201 T UNIT BL and H301-T UNIT BL
User interface	OKO-Touch (to be ordered separately)
Web Operation	Through Smart Box (to be ordered separately)
Filtering device	PTFE membrane with 0.2 µm pores
SDK	Available for download through website
Sensor Calibration mechanism	i) Comparison with external meter ii) Span Gas
Recommended sensor calibration period	CO ₂ one year; O ₂ one year



OkO Touch





Smart Box



Air Pump

CO₂ - O₂ UNIT BL [0-10;1-18]



Flow rate (l/min)	CO ₂ SP (%)	Mean (%)	Max (%)	Min (%)	Std (%)
0.2	3.0	2.99	3.05	2.95	0.02
	5.0	5.00	5.08	4.89	0.04
	8.0	8.00	8.15	7.88	0.06
0.4	3.0	3.01	3.05	2.95	0.02
	5.0	5.01	5.25	4.93	0.04
	8.0	8.00	8.07	7.93	0.03
0.6	3.0	3.01	3.05	2.95	0.02
	5.0	5.03	5.08	4.98	0.02
	8.0	8.02	8.10	7.93	0.03
0.8	3.0	3.00	3.09	2.96	0.03
	5.0	4.99	5.07	4.93	0.03
	8.0	7.99	8.05	7.93	0.03

Flow rate (l/min)	O ₂ SP (%)	Mean (%)	Min (%)	Max (%)	Std (%)
0.2	5.0	5.01	5.19	4.85	0.06
	10.0	10.00	10.10	9.80	0.05
	15.0	14.99	15.05	14.91	0.03
0.4	5.0	4.98	5.03	4.94	0.02
	10.0	10.01	10.25	9.93	0.04
	15.0	15.00	15.07	14.95	0.02
0.6	5.0	5.00	5.09	4.94	0.03
	10.0	9.99	10.32	9.87	0.06
	15.0	14.99	15.09	14.92	0.03
0.8	5.0	4.99	5.10	4.77	0.06
	10.0	9.99	10.06	9.84	0.04
	15.0	14.99	15.06	14.87	0.03

